



TD-1400 Stretch Series

STANDARD FEATURES

- Capacity:** 16,000 Lbs. G.V.W.R.
- Accommodates:** 1200-1400 Gallon Poly, Stainless Steel or Fiberglass Tank or a 7-Ton Dry Fertilizer Box
- Suspension:** 6-Leaf x 2" Underslung Slipper Springs
- Axes:** 3" x 3" x .25" Heavy Wall Tubing
- Spindles:** 2.25" Diameter, 1144 Cold Rolled Shaft
- Hubs:** 783, 6-Bolt on 6" Bolt Circle, 4,570 Lbs. Each
- Wheels:** 15" x 10" x 6 - 6"
- Tires:** Priced Separately, See Tire Options
- Frame:** 7" Structural Channel
- Jack:** 2,000 Lb. Top-Wind
- Dimensions:** Frame Width-71 Inches, Overall Length-15 Feet, 8 Inches
- Hitch:** Adjustable Height Clevis
- Other:** (2) D.O.T. Safety Chains
Platform in Tongue for Pump
Hose Storage Hooks
6" Wide Cross Members
(2) 12" x 12" Fill Steps
Conspicuity Tape



OPTIONS

- Tires:** 12.5L x 15 10-Ply Implement, 16" or 16.5" High-Speed Truck Tires
- Brakes:** Electric or Hydraulic Surge
- Axes:** High Speed Axles with 8-Bolt Hubs and Wheels, Rubber Torsion Axles with 8-Bolt Hubs and Wheels
- Hitch:** Ball Coupler, Lunette Eye or Gooseneck
- Other:** Fenders or 6' Walk-On Fill Platforms, Sealed Beam LED Lights (D.O.T. Approved), Hose Storage Stand, Chemical Inductor Stand, Extra Frame Length and Platform to Accommodate Chemical Storage Containers, ATV and Mini-Bulk Tanks. Other customer requirements available.

We reserve the right to make specification changes without notice.

Distributed By