

TD1635 STANDARD MODEL



TD1635 With OPTIONAL FRONT PLATFORM



STANDARD FEATURES:

CAPACITY.....	20,000 LBS. G.V.W.R.
TANK SIZE.....	1635 - GALLON NORWESCO
SUSPENSION.....	2" X 8-LEAF UNDER-SLUNG SLIPPER SPRING
AXLE.....	3" X 3" X .375" HEAVY WALL TUBING
SPINDLES.....	2.50" DIAMETER, 1144 COLD ROLLED SHAFT
HUBS.....	8-BOLT ON 8" BOLT CIRCLE, 5,790 LBS. CAPACITY EACH
WHEELS.....	22.5" X 8.25" X 8 - 8", 6,000 LBS. CAPACITY EACH
BRAKES.....	2-WHEEL HYDRAULIC SURGE ON FRONT AXLE
FRAME.....	7" STRUCTURAL CHANNEL
JACK.....	DROP LEG, TOP-WIND, 10,000-LB CAPACITY
LIGHTS.....	D.O.T, LED STOP, TURN, TAIL MARKER, & LICENSE LAMPS WITH 7-WAY CONNECTOR AND WIRING ENCLOSED IN CONDUIT
COUPLER.....	CLEVIS, ADJUSTABLE HEIGHT
SAFETY CHAINS...	(2) D.O.T. 1/2" X 40" WITH HOOK, I.D. TAG, SAFETY LATCH AND MOUNTING BRACKET
OTHER.....	PUMP PLATFORM IN TONGUE, HOSE STORAGE HOOK, (2) 12" X 12" FILL STEPS, OPERATOR'S MANUALS, AND SAFETY DECALS
WARRANTY.....	5-YEAR WARRANTY ON MANUFACTURED PRODUCTS



Trailer Frame

OPTIONS:

BRAKES.....	4-WHEEL HYDRAULIC SURGE OR ELECTRIC
COUPLER.....	BALL OR PINTLE RING
OTHER.....	PLATFORM IN FRONT OF TANK WITH RAILING, FENDERS, HOSE STAND, PUMP, HOSE KIT
OTHER WHEEL/TIRE.....	NEW 11:00 X 22.5 HIGHWAY TIRES USED 11:00 X 22.5 EXTRA GOOD TRUCK TIRES

"Quality Products Since 1943"