

DC6050 Transport Trailer



TC9075 Transport Trailer



IMPORTANT:

Must Be Transported With Tanks Empty

Trailer Weight Without Tanks: DC6050 - 2,560 Lbs. / TC9075 - 3,042 Lbs.

(Tanks Not Included)

TRAILERS INCLUDES:

- 2" Diameter 1144 Cold Rolled Spindles
- 611 Hubs With 6-Bolt Circle, 3,600-Lbs. Capacity Each
- 15" x 8" 6-6" Wheels, 3,800-Lbs. Capacity Each
- 11L x 15 8-Ply Tubeless Tire
- 6" Structural Channel Main Frame
- Hydraulic Lift System with Double Acting Hydraulic Pump and Manual Pump Lever
- Dual Transport Height Sliding Locks with Dual Lock Pins and Retaining Chain
- Ag Transport Lights / Rear Conspicuity Tape with 7-Way RV Wiring Connector
- (2) Hose Storage Holder Hooks Per Cone
- Top Wind Tongue Jack
- Adjustable Clevis Hitch
- D.O.T. Safety Chains
- Operator's Manual Canister
- Platform in Tongue for Pump Mounting
- DC6050 Accommodates: (2) 2,500 or (2) 3,000 Gallon 15 Degree Cone Bottom Tanks (Tanks Not Included)
- TC9075 Accommodates: (3) 2,500 or (3) 3,000 Gallon 15 Degree Cone Bottom Tanks (Tanks Not Included)



TRAILER ONLY

"Quality Products Since 1943"

DUO LIFT® Manufacturing
Company, Inc.

CONE BOTTOM TRANSPORT TRAILERS
DC6050 & TC9075



MODEL: DC6050 Shown in Field Storage Position



MODEL: TC9075 Shown in Transport Position



TRAILER ONLY



Front Hitch, Tongue Jack
and Safety Chains



MODEL: TC9075 Front View



Hydraulic Lift System for
DC6050 and TC9075